

# MODEL NO UV CASE 15L

Sanitisation Time : ~12 mins



<b>Operating Principle</b>	Short wave UV-C radiation (peak at 253.7 nm) based disinfecting of surfaces from germs, bacteria and viruses.
<b>External Dimension : H X W X D (mm)</b>	127.6 X 427.8 X 382.4
<b>External Volume (approximate litres)</b>	21
<b>Internal Dimension-Usable : H X W X D (mm)</b>	124 X 326 X 380
<b>Internal Usable Volume (litre)</b>	~15
<b>Weight (Kg)</b>	8
<b>Recommended Sanitisation Time (approx. min)</b>	12
<b>UV-C lights: Wattage/Tube (W)</b>	11
<b>UV-C lights: Wattage-Total (W)</b>	22
<b>UV-C lights: Life /Tube (hour)</b>	11000
<b>Lid Opening</b>	Ergonomic top opening design
<b>Cycle Time</b>	Manual control
<b>Audio Visual Alarm</b>	NA
<b>Auto UV-C Cut-off Safety Switch</b>	Yes
<b>Electrical Specifications</b>	Supply voltage 220V ~240V   Supply current 5A   Operating frequency 47 ~53Hz
<b>Warranty</b>	1 year standard product warranty**

**Housing :** Rugged & durable mild steel(MS) powder coated housing | Safe from UV leakage | Produced as per highest & consistent QA/QC norms

# MODEL NO UV CASE 30L

Sanitisation Time : ~5 mins



<b>Operating Principle</b>	Short wave UV-C radiation(peak at 253.7 nm) based disinfecting of surfaces from germs, bacteria and viruses.
<b>External Dimension : H X W X D (mm)</b>	325 X 297.8 X 476.8
<b>External Volume (approximate litres)</b>	46
<b>Internal Dimension-Usable : H X W X D (mm)</b>	298 X 236 X 417
<b>Internal Usable Volume (litre)</b>	~30
<b>Weight (Kg)</b>	14.5
<b>Recommended Sanitisation Time (approx. min)</b>	5
<b>UV-C lights: Wattage/Tube (W)</b>	11
<b>UV-C lights: Wattage-Total (W)</b>	44
<b>UV-C lights: Life /Tube (hour)</b>	11000
<b>Lid Opening</b>	Ergonomic front opening design
<b>Cycle Time</b>	Predefined
<b>Audio Visual Alarm</b>	Yes
<b>Auto UV-C Cut-off Safety Switch</b>	Yes
<b>Electrical Specifications</b>	Supply voltage 220V ~240V   Supply current 5A   Operating frequency 47 ~53 Hz
<b>Warranty</b>	1 year standard product warranty**

**Housing :** Rugged & durable mild steel(MS) powder coated housing | Safe from UV leakage | Produced as per highest & consistent QA/QC norms

# MODEL NO **UV CASE 54L**

Sanitisation Time : ~5 mins



<b>Operating Principle</b>	Short wave UV-C radiation(peak at 253.7 nm) based disinfecting of surfaces from germs, bacteria and viruses.
<b>External Dimension : H X W X D (mm)</b>	350 X 540 X 519.2
<b>External Volume (approximate litres)</b>	98
<b>Internal Dimension-Usable : H X W X D (mm)</b>	241 X 437 X 510
<b>Internal Usable Volume (litre)</b>	~54
<b>Weight (Kg)</b>	22
<b>Recommended Sanitisation Time (approx. min)</b>	5
<b>UV-C lights: Wattage/Tube (W)</b>	11
<b>UV-C lights: Wattage-Total (W)</b>	66
<b>UV-C lights: Life /Tube (hour)</b>	11000
<b>Lid Opening</b>	Ergonomic front opening design
<b>Cycle Time</b>	User selectable
<b>Audio Visual Alarm</b>	Yes
<b>Auto UV-C Cut-off Safety Switch</b>	Yes
<b>Electrical Specifications</b>	Supply voltage 220V ~240V   Supply current 5A   Operating frequency 47 ~53 Hz
<b>Warranty</b>	1 year standard product warranty**

**Housing :** Rugged & durable mild steel(MS) powder coated housing | Safe from UV leakage | Produced as per highest & consistent QA/QC norms