

# HS-45 Deposit Safe



**HS-45** deposit safe has a top opening of 18mm x 115mm for your deposit of envelope or cash. It is equipped with dual locking system for both combination and electronic safe.

**Boltwork:** The door is secured by two 20mm in diameter steel moving bolts at the front end and fixed bolts at the rear edge

**Locking:** The locking mechanism is controlled by keylock and 3-wheel combination lock for HS-45C and keylock and electronic lock for HS-45E. The numbers are changeable at will by the user.



**C-DIAL**



**DIGITAL**



External Dimensions (mm)			Internal Dimensions (mm)			Weight (kg)
Height	Width	Depth	Height	Width	Depth	
450	330	335	355	255	230	40

- Depth exclusive of lock



Marketed and Supported by:  
**HIS InterSecure Solutions (S) Pte Ltd**  
 1092 Lower Delta Road #04-06/07  
 Mapletree Industrial Estate  
 Singapore 169203  
 Tel: 6272 7375 Fax : 6273 3073  
 Website: [www.hiss.com.sg](http://www.hiss.com.sg)

*This Catalogue has been designed for distribution throughout many international markets. Thus, some specifications, comparisons and information set forth herein may vary in all markets. The manufacturer's policy reserved the right to change the specifications without prior notice for continuous improvement.*