

# HS-52



**HS-52** home safe is tested to provide 60 minutes of fire protection for your paper records in accordance to KSG 4500 standard. It is equipped with dual locking system for both combination and electronic safe.

**Body:** Comprising of international standard steel filled with fireproof mixture.

**Boltwork:** The door is secured by two 20mm in diameter steel moving bolts at the front end and fixed bolts at the rear edge

**Locking:** The locking mechanism is controlled by one 3-wheel combination lock for HS-52C and electronic lock for HS-52E. The numbers are changeable at will by the user.



C-DIAL



DIGITAL

External Dimensions (mm)			Internal Dimensions (mm)			Weight (kg)	Accessory
Height	Width	Depth	Height	Width	Depth		
520	430	520	395	325	325	90	1 tray/1 shelf

- Height inclusive of legs
- Depth inclusive of handle



Marketed and Supported by:  
**HIS InterSecure Solutions (S) Pte Ltd**  
 1092 Lower Delta Road #04-06/07  
 Tiong Bahru Industrial Estate  
 Singapore 169203  
 Tel: 6272 7375 Fax : 6273 3073  
 Website: www.hiss.com.sg

*This Catalogue has been designed for distribution throughout many international markets. Thus, some specifications, comparisons and information set forth herein may vary in all markets. The manufacturer's policy reserved the right to change the specifications without prior notice for continuous improvement.*