

TL-105C

TL-105C office safe is tested to provide 120 minutes of fire protection for your paper records in accordance to KSG 4500 standard. It is equipped with dual locking.

Body: Comprising of international standard P.O. steel filled with fireproof mixture.

Boltwork: The door is secured by a series of 22mm in diameter steel moving bolts at the front end, top, bottom and fixed bolts at the rear edge.

Locking: The locking mechanism is controlled by one keylock and one combination lock. The numbers are changeable at will by the user.



External Dimensions (mm)			Internal Dimensions (mm)			Weight (kg)	Accessory
Height	Width	Depth	Height	Width	Depth		
1,030	580	530	810	460	325	235	1 drawer + 2 shelves

- Height inclusive of legs
- Depth inclusive of handle



Marketed and Supported by:
HIS InterSecure Solutions (S) Pte Ltd
 203 Henderson Road #02-10
 Wing A, Henderson Industrial Park
 Singapore 159546
 Tel: 6272 7375 Fax: 6273 3073
 Website: www.hiss.com.sg

TL-105E

TL-105E office safe is tested to provide 120 minutes of fire protection for your paper records in accordance to KSG 4500 standard. It is equipped with dual locking.

Body: Comprising of international standard P.O. steel filled with fireproof mixture.

Boltwork: The door is secured by a series of 22mm in diameter steel moving bolts at the front end, top, bottom and fixed bolts at the rear edge.

Locking: The locking mechanism is controlled by one keylock and one Digital lock. The numbers are changeable at will by the user.



External Dimensions (mm)			Internal Dimensions (mm)			Weight (kg)	Accessory
Height	Width	Depth	Height	Width	Depth		
1,030	580	530	810	460	325	235	1 drawer + 2 shelves

- Height inclusive of legs
- Depth inclusive of handle



Marketed and Supported by:
HIS InterSecure Solutions (S) Pte Ltd
 203 Henderson Road #02-10
 Wing A, Henderson Industrial Park
 Singapore 159546
 Tel: 6272 7375 Fax: 6273 3073
 Website: www.hiss.com.sg